




KFG Gages ● Biaxial 350Ω/Biaxial 350Ω for torque measurement

| Pattern | Leadwire Cable - Type and Shape | Operating Temp. Range | Leadwire Length | Model | |
|--|--|---|-----------------|------------------------|------------------------|
|  <p>KFG-2-350-D1-11 16 23 27</p> <p>Biaxial, 0°/90°</p> <ul style="list-style-type: none"> ● Base Size 10 x 8.5 mm ● Gage Length 2 mm ● Gage Resistance 350Ω ● Pieces per Pack 10 | Vinyl-coated flat 3-wire cable L-7 (L-10 for 6m or longer) | -10 to 80°C | 1m | KFG-2-350-D1-11 L1M3S | |
| | | | | 3m | KFG-2-350-D1-11 L3M3S |
| | | | | 5m | KFG-2-350-D1-11 L5M3S |
| | | Vinyl-coated flat 2-wire cable L-6 (L-9 for 6m or longer) | -10 to 80°C | 1m | KFG-2-350-D1-11 L1M2S |
| | | | | 3m | KFG-2-350-D1-11 L3M2S |
| | | | | 5m | KFG-2-350-D1-11 L5M2S |
| | | Middle-temperature 3-wire cable L-12 | -100 to 150°C | 1m | KFG-2-350-D1-11 R1M3 |
| | | | | 3m | KFG-2-350-D1-11 R3M3 |
| | | | | 5m | KFG-2-350-D1-11 R5M3 |
| | | Middle-temperature 2-wire cable L-11 | -100 to 150°C | 1m | KFG-2-350-D1-11 R1M2 |
| | | 3m | | KFG-2-350-D1-11 R3M2 | |
| | | 5m | | KFG-2-350-D1-11 R5M2 | |
| | 2 polyester-coated copper wires | -196 to 150°C | 5cm | KFG-2-350-D1-11 N5C2 | |
| | | | 15cm | KFG-2-350-D1-11 N15C2 | |
| | | | 30cm | KFG-2-350-D1-11 N30C2 | |
| | Silver-clad copper wires | -196 to 150°C | 25mm | KFG-2-350-D1-11 | |
| | | | | | |
| | | | | | |
|  <p>KFG-2-350-D2-11 16 23 27</p> <p>Biaxial, 0°/90° for torque measurement</p> <ul style="list-style-type: none"> ● Base Size 12 x 6.8 mm ● Gage Length 2 mm ● Gage Resistance 350Ω ● Pieces per Pack 10 | Vinyl-coated flat 3-wire cable L-7 (L-10 for 6m or longer) | -10 to 80°C | 1m | KFG-2-350-D2-11 L1M3R | |
| | | | | 3m | KFG-2-350-D2-11 L3M3R |
| | | | | 5m | KFG-2-350-D2-11 L5M3R |
| | | Middle-temperature 3-wire cable L-12 | -100 to 150°C | 1m | KFG-2-350-D2-11 R1M3 |
| | | | | 3m | KFG-2-350-D2-11 R3M3 |
| | | | | 5m | KFG-2-350-D2-11 R5M3 |
| | | Polyester-coated copper wires | -196 to 150°C | 5cm | KFG-2-350-D2-11 N5C2 |
| | | | | 15cm | KFG-2-350-D2-11 N15C2 |
| | | | | 30cm | KFG-2-350-D2-11 N30C2 |
| | | Silver-clad copper wires | -196 to 150°C | 25mm | KFG-2-350-D2-11 |
| | | | | | |
| | | | | | |
|  <p>KFG-2-350-D31-11 16 23 27</p> <p>Biaxial, 0°/90° for torque measurement</p> <ul style="list-style-type: none"> ● Base Size 10.5 x 6.5 mm ● Gage Length 2 mm ● Gage Resistance 350Ω ● Pieces per Pack 10 | Vinyl-coated flat 3-wire cable L-7 (L-10 for 6m or longer) | -10 to 80°C | 1m | KFG-2-350-D31-11 L1M3R | |
| | | | | 3m | KFG-2-350-D31-11 L3M3R |
| | | | | 5m | KFG-2-350-D31-11 L5M3R |
| | | Middle-temperature 3-wire cable L-12 | -100 to 150°C | 1m | KFG-2-350-D31-11 R1M3 |
| | | | | 3m | KFG-2-350-D31-11 R3M3 |
| | | | | 5m | KFG-2-350-D31-11 R5M3 |
| | | Polyester-coated copper wires | -196 to 150°C | 5cm | KFG-2-350-D31-11 N5C2 |
| | | | | 15cm | KFG-2-350-D31-11 N15C2 |
| | | | | 30cm | KFG-2-350-D31-11 N30C2 |
| | | Silver-clad copper wires | -196 to 150°C | 25mm | KFG-2-350-D31-11 |
| | | | | | |
| | | | | | |